## Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

## **Listing of Claims:**

Claim 1 (original): Handle (20) or handles for a blower (10) carried on the back of an operator, said handle (10) or handles are placed on a stiff section (15) of a extending tube (13) from the blower blower characterised in that a longitudinal axle (A) of the handle (20) or handles is places outside the circumference of the stiff section (15) of the blower tube (13) when seen in a plane perpendicular to the longitudinal axle of the stiff of the blower tube (13), and that section(15) projection of the longitudinal axle (A) of the handle (20) in said plane is parallel to a straight line (L) extending through the geometrical centre of the cross section of the stiff section(15) of the blower tube (13).

Claim 2 (original): Handle (20) according to claim 1, characterised in that the cross section of the stiff section (15) to the blower tube (13) is a circle.

Claim 3 (original): Handle according to claim 1 or 2, characterised in that the handle (20) or handles are placed so that the distance from the outer side of the blower tube (13) to a surface (25) on the handle where the operators

hand is placed during normal use of the tool not exceeds 100 millimeters.

Claim 4 (original): Handle according to claim 3, characterised in that the distance is between 15 to 60 millimeters.

Claim 5 (currently amended): Handle according to claim  $1, \frac{2}{2}, \frac{3}{3}$  or  $\frac{4}{3}$ , characterised in that the handle (20) or handles is movable around the circumference of the blower tube (13).

Claim 6 (currently amended): Handle according to claim 1,2, 3, 4 or 5, characterised in that the position of the handle (20) or handles in axial direction along the tube (13) is adjustable.

Claim 7 (currently amended): Handle according to any of the proceeding claims claim 1, characterised in that the blower tube (13) is provided with one handle (20) or handle bar comprising two handles.

Claim 8 (currently amended): Handle according to [any of] claim 1 [to 7], characterised in that the handle (20) or handles are placed on a curved arm (21) so that the position of the handle (20) or handles are closer to the

operator than the position where the curved arm (21) is secured to the blower tube (13).

Claim 9 (original): Handle according to claim 8, characterised in that curved arm (21) is secured to the blower tube (13) by a loop (22) surrounding the blower tube (13).

Claim 10 (original): Handle according to claim 9, characterised in that the loop (22) is secured to the blower tube (13) by a screw (24) activated by a wheel (23).

Claim 11 (original): Handle according to claim 10, characterised in that the curved arm (21) and the handle (20) is turnable when the screw (24) is released so that the angle between the longitudinal axle (A) of the handle (20) in relation to the longitudinal axle of the blower tube (13) is changed.